



### Carpet Details: Super (40oz) / Supreme (50oz) / Elite (60oz)

Specification		General Information	
Construction:	Tufted	<p><b>Pile reversal:</b> All cut pile carpets can suffer from pile reversal and in certain instances this may become permanently bent or distorted for no specific reason that research has yet identified, giving areas of light and shade. This is also known as "shading" or "watermarking". It is not a defect in manufacture, it only occurs in a small percentage of all carpets and no liability whatsoever can be accepted by the manufacturer in respect of it.</p> <p><b>Pile pressure:</b> All cut pile carpets are liable to show light and dark patches resulting from disturbance of the pile created by foot traffic or brushing, This is a normal feature and is not a defect in manufacture and no liability whatsoever can be accepted by the manufacturer in respect of it.</p> <p><b>Pale shades:</b> We include within our collection a number of pale shades. Primarily these are used as top or highlight colours. These more delicate shades will invariably tend to soil more quickly and give a lower of light fastness than the norm, and may show natural blemishes within the fibre that tend to be masked in deeper shades containing a greater quantity of dyestuff.</p>	
Pile Weight:	40oz: 1250g/m <sup>2</sup> / 50oz: 1600g/m <sup>2</sup> / 60oz: 1900g/m <sup>2</sup> - Stripes in 40oz only		
Backing:	Action		
Pile Yarn Content:	80% Wool, 20% Polypropylene		
Pile Height:	7mm		
Yarn count & tex	2 Ply/47's, R660 tex		
Warranty:	10 years		
Width:	4m & 5m (Stripes in 4m only)		
TOG:	40oz: 1.2 / 50oz: 1.4 / 60oz: 1.5		
Tested for			
<p><u>Suitability</u> Heavy Domestic/General Contract Class 33 BS EN 1307:2005</p> <p><u>Flammability</u> BS4790 (hot metal nut) : BS5287      Low radius of ignition Methenamine pill : BS ISO6925      Pass Nordic Fire Test (NT007): The carpet meets the requirement of Class L - Nordic Ministry of the Environment DIN 4102 part 1 (IFB) - Class B1</p> <p><u>Insect Resistant</u>      Yes</p> <p><u>Suitability for Stairs:</u> Yes (For maximum performance we recommend the use of an approved stair nosing and the movement of carpet every 6 months from tread to rise).</p> <p><u>Static Propensity</u> Low propensity to static down to 40% RH</p>		<p>Available in 4m &amp; 5m rolls. Regular Nationwide delivery service Fashionable colours to meet a wide variety of interior styles. Ease of maintenance. Made in: UK. All colours available from stock for immediate call off.</p>	
Installation			
<p>To be installed in accordance with BS5325 "Code of Practice for the Installation of Floor Coverings" and NICF manual.</p> <p>For quantity orders requiring colour matching, please state at the time of ordering.</p> <p>All samples may not be from the same production batch as current stock and therefore should be used as a guide and not as an exact match.</p> <p>Colour variations: There may be colour variations/shade variations between each batch of carpet as well as with undyed materials.</p> <p>Undyed Wool: Due to the inherent natural variations in undyed wool and the current blending techniques, there may be noticeable shade variations between the colours used in the same material and the actual production. Pattern match cannot be guaranteed with any tufted patterned carpet.</p>			
Maintenance			
<p>Hugh Mackay &amp; Whitestone Weavers recommend that this carpet is maintained in accordance with an agreed maintenance schedule which should include the following:</p> <ol style="list-style-type: none"> <li>Vacuum regularly.</li> <li>Remove spills immediately.</li> <li>Professionally clean as required.</li> </ol>			



# HUGH MACKAY

---

carpets

## Riverside Twist Product Profile



### Carpet Images



Avon



Black Water



Cool Grey



Desert Sand



Doeskin



Fawn



Harvest



Ivory Cream



Maize



Pewter



Platinum



Seal



Steel



Stone



Taupe



Woodsmoke



Hardwick Beige Stripe



Jacobs Grey Stripe





**HUGH MACKAY**  
carpets

Riverside Twist Product Profile



Carpet Images



Avon